

IoT Wireless Datalogger for Temperature and Humidity from external probe, CO₂ and Atmospheric Pressure from built-in sensors with built-in 4G modem

code: U4442G



4G datalogger is designed to record temperature and humidity from external Digi/E series probe, atmospheric pressure and CO₂ from internal sensors. In case of exceeded set limits, SMS and JSON messages can be sent via 4G data connection. Measured values can be sent to the internet storage [COMET Cloud](#), which is a complete monitoring, alarm and analysis system.

It is also possible to set the regular sending of JSON messages to COMET Database, the sending interval is adjustable. Alarms are also indicated locally by LED, LCD and acoustically by built-in beeper. The recording is performed in a non-volatile electronic memory. The data can be transferred to a PC via included USB-C cable.

4G recorder **includes Traceable calibration certificate** with declared metrological traceability of etalons is based on requirements of **EN ISO/IEC 17025 standard**.

With a newly purchased IoT wireless datalogger with a built-in modem, you receive 3 months of [COMET Cloud](#) for free; a full year of operation in [COMET Cloud](#) then requires [1 credit](#).

Technical data

TEMPERATURE SENSOR	
Measuring range	according to the connected probe Digi/E
Accuracy	according to the connected probe Digi/E
Resolution	0.1 °C
Response time	according to the connected probe Digi/E
HUMIDITY SENSOR	
Measuring range	according to the connected probe Digi/E
Accuracy	according to the connected probe Digi/E
Resolution	0.1% RH
DEW POINT	
Measuring range	according to the connected probe Digi/E
Accuracy	according to the connected probe Digi/E
Resolution	0.1 °C
CO ₂ SENSOR	
Measuring range	0 to 5000 ppm
Accuracy	±(50ppm +2% from reading) at 25°C and 1013hPa
Resolution	1 ppm
ATMOSPHERIC PRESSURE SENSOR SENSOR	
Measuring range	600 to 1100 hPa
Accuracy	±1.3 hPa at 23 °C from 800 to 1100 hPa
Resolution	0.1 hPa
4G MODEM PARAMETERS	

LTE Cat 1	LTE FDD/GSM/GPRS/EDGE
Supported network types	GSM/GPRS/EDGE 900/1800 MHz LTE FDD B1/B3/B5/B7/B8/B20
GENERAL TECHNICAL DATA	
Operating temperature	-20 to +60 °C
Channels	connector for external Digi/E series probe, built-in (internal) atmospheric and CO ₂ concentration sensor
Memory	500,000 values in noncyclic logging mode; 350,000 values in cyclic record mode
Recording interval to the internal memory	adjustable from 1 second to 24 hours
Recording interval to the COMET Cloud	from 5 minutes
Interval for measuring and evaluating alarms	adjustable 1 s, 10 s, 1 min
Recording mode	noncyclic - data logging stops after filling the memory cyclic - after filling memory oldest data is overwritten by new
Real time clock	year, leap year, month, day, hour, minute, second
Power	rechargeable Li-Ion battery A8200, 3.6V/5200mAh
Protection class	IP20
Dimensions	61 x 93 x 53 mm, with antenna 120 x 93 x 53 mm
Weight (including batteries)	approx. 260 g
Warranty	3 years