



VI-3003

- Small design
- Power supply via PoE or locally
- PoE 802.3af/at 30W
- 3 x 10/100/1000 BaseT
- Extended temperature range

The VI-3003 is a 3-port IP switch with PoE. Its compact design and wide operating temperature range make it ideal for use in remote locations, including outdoors. The switch can be powered by PoE and itself supplies PoE to the connected end devices. The switch can also be powered locally. The VI-3003 can also be used in a cascade, connecting several locations, each with one end device, with just one cable.

Product information

Brief description

3-port IP switch with PoE

System Notes

CAUTION

Do not connect a non-PoE device to port 2 of the Vi3003. This may damage the non-PoE device. If you need to connect a non-PoE device to port 2, use a VI-0025 between port 2 and the RJ45 connector of the non-PoE device. The VI-0025 only forwards the data from the Ethernet connection and blocks the PoE on this line.

Technical data

Copper Ports	3 x 10/100/1000TX, RJ45 1 x PoE IN 60W 2 x PoE OUT (2 x 30W) PoE OUT means that the switch is a PSE (Power Sourcing Device) and powers a camera, for example PoE IN means that the switch is a PD (Powered Device) and is powered by PoE.
Supply Voltage	In PoE operation, power supply is provided via Po If only data is transmitted and PoE is not available, the VI-3003 must be powered

locally

Local power supply: 52-56 VDC, hollow connector, for example VI-1120.

IP Schutzart	IP33
Operating temperature	-40°C to +75°C
Power Loss	34 BTU/h
Dimensions	25 x 45 x 105mm (HxWxL)
Weight	Gross weight: 0.19 kg Net weight: 0.12 kg